Title

Prepn. of polymeric iron sulphate - by oxidising acidic aq. soln. of ferrous sulphate at ambient pressure in absence of oxidn..

Patent Data

Patent Family

WO9523765 A1 19950908 DW1995-41 C01G-049/14 Eng 22p * AP: 1995WO-GB00483 19950306 DSNW: AM AU BB BG BR BY CA CN CZ GB GE HU JP KG KP KR KZ LK LT LV MD MG MN NO NZ PL RO RU SI SK TJ TT UA US UZ VN DSRW: AT BE CH DE DK ES FR GB GR IE IT KE LU MC MW NL OA PT SD SE SZ UG

AU9518541 A 19950918 DW1995-51 C01G-049/14 FD: Based on WO9523765 AP: 1995AU-0018541 19950306

EP-749402 A1 19961227 DW1997-05 C01G-049/14 Eng FD: Based on WO9523765 AP: 1995EP-0910624 19950306; 1995WO-GB00483 19950306 DSR: AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

US5785862 A 19980728 DW1998-37 C01G-049/14 FD: Based on WO9523765 AP: 1995WO-GB00483 19950306; 1996US-0700534 19960918

AU-698392 B 19981029 DW1999-04 C01G-049/14 FD: Previous Publ. AU9518541; Based on WO9523765 AP: 1995AU-0018541 19950306

Priority n° 1994GB-0004191 19940304

Covered countries 58

Publications count 5
Cited patents A

AU-464517; US2905533

Abstract

Basic Abstract

WO9523765 A Prepn. of a polymeric form of Fe2(SO4)3 comprises oxidising an acidic aq. soln. of ferrous sulphate4 to form Fe2(SO4)3 in the soln. at ambient pressure and in the absence of oxidn. catalyst. The Fe2(SO4)3 is at least partially hydrolysed by the addn. to the soln. of at least one base and the Fe2(SO4)3 is kept in contact with the base at a temp. for sufficient time for polymerisation of at least partially hydrolysed Fe2(SO4)3.

Also claimed is a method of treating water using the sulphate.

he pH of the aq. soln. prior to oxidn. is < 2 (esp. 0.8-1.5). The oxidn. is a one step oxidn. stage, and the oxidn. temp. is < 110deg.C (pref. 15-50)deg.C. The oxidn. time is up to 3 (pref. 1) hr. The oxidn. step concn. of Fe2+ ions in soln. is < 2.5 (pref. 0.25)% Fe2+/Fe3+.

During the hydrolysis step, Fe(III) hydrolysis species of formula (A) and polynuclear complexes of Fe(III) of formula (B) form as the polymeric form of Fe2(SO4)3. The hydrolysis stage is carried out immediately after the oxidn. stage without removing or otherwise purifying the Fe2(SO4)3 formed.

The oxidising agent comprises ozone, HNO3, peroxide, perchlorate and/or persulphate (esp. HNO3 and/or H2O2). The aq. soln. comprises FeSO4 and H2SO4. The base comprises an hydroxide or a bicarbonate of an alkali metal.

USE - The polymeric Fe2(SO4)3 is useful as a coagulant or flocculant and for purifying and/or decolourising water and reducing pollutants in industrial and/or municipal wastewaters.

ADVANTAGE - The polymeric Fe2(SO4)3 (PFS) is obtd. by a more economical process and confers better performance. (Dwg.0/0)

Patentee, Inventor

Patent assignee (UNLO) IMPERIAL COLLEGE SCI TECHNOLOGY & MED

Inventor(s) GRAHAM NJD; JIANG J

IPC C01G-049/14 C02F-001/52

Accession Codes

Number 1995-320508 [41] Sec. No. C1995-142368

Codes

Manual Codes CPI: D04-A01B D04-B E35-U04

Derwent Classes D15 E31

Updates Codes

Basic update code 1995-41

Equiv. update code 1995-51; 1998-37; 1999-04